

BIRTH CERTIFICATE

FRONT WHEEL

1 WHEEL SPECIFICATION

Hub: _____
 Rim: _____
 Spoke: _____
 Nipples: _____
 Spoke count: _____ Lacing pattern: _____

NON-DRIVE SIDE SPOKES

_____ mm

DRIVE SIDE SPOKES


_____ mm

Lateral runout +/- mm


Radial runout +/- mm



2 WEIGHT

Hub: _____ g
 Rim: _____ g
 Spokes: _____ g
 _____ g

3 TENSION



LEFT SIDE RIGHT SIDE

Average spoke tension: _____ kgF

Minimum spoke tension: _____ kgF

Maximum spoke tension: _____ kgF

REAR WHEEL

1 WHEEL SPECIFICATION

Hub: _____
 Rim: _____
 Spoke: _____
 Nipples: _____
 Spoke count: _____ Lacing pattern: _____

NON-DRIVE SIDE SPOKES

_____ mm

DRIVE SIDE SPOKES


_____ mm

Lateral runout +/- mm


Radial runout +/- mm



2 WEIGHT

Hub: _____ g
 Rim: _____ g
 Spokes: _____ g
 _____ g

3 TENSION



LEFT SIDE RIGHT SIDE

Average spoke tension: _____ kgF

Minimum spoke tension: _____ kgF

Maximum spoke tension: _____ kgF

Powered by



CUSTOMER

ASSEMBLED BY

